



ELIT 110II, CAT III



Voltage tester CAT III with low impedance test for detection of ghost voltages

Technical description

Voltage tests in CAT III for up to 400V AC / DC with indication of voltage level via LEDs. The instrument has divisions from $\pm 6V$, 12V, 24V, 50V, 120V, 230V and 400V AC/DC. The frequency range of the instrument is from DC to 65Hz. The instrument does not use batteries. In addition, the instrument has LI-TEST (low impedance test) which loads the circuit it is tested on to detect ghost voltages. Delivered in carrying case with user manual.

Voltage AC 6-400V, Voltage DC 6-400V, Polarity \pm , Works without battery, Safety IEC1010-1, Overvoltage category CAT IV 600V
Low impedance test 270k,
Measuring tips 2 / 4mm

Advantages:



Product name/ Art.nr/ GTIN	
Product name/ Art.nr/ GTIN	ELIT 110II, CAT III/ 10290001/ 7070810000029
According to:	---
Type of test	2-pole
Voltage indication	LED
Voltage measuring range	6 - 400 Volt
Length	260 Millimetre
Blade length	20 Millimetre
Blade width	4 Millimetre
Internal base load	No
Load switchable	No
Indication of direction of field rotation	No
Continuity test	No
Single pole phase indication	No
Contact less voltage detection	No
Data hold	No
Background lighting LC-indication	No
Test prod protection	Yes
Measuring point lightning	No
Usable at precipitation	Yes
Current supply	From test object (without battery)
Measuring circuit category	CAT III