

ELIT 140E, 0,01mA - 300A



Compact current clamp with good accuracy for precise measurement of leakage current.

Technical description

Leakage current clamp with 10 A resolution. Large clamp jaw of 40mm. Low battery indication. Overload indication. Small physical size, pocket size. Data hold to freeze measured value on display. Can also be used as a standard current clamp as it measures up to 300AAC. Delivered in a bag with battery and Norwegian instructions.

Advantages:



Product name/ Art.nr/ GTIN	FLIT 140F 0.04mA 200A/40200000/707004000070	
	ELIT 140E, 0,01mA - 300A/ 10300000/ 7070810000272	
According to:		
Indication	Digital	
Analogue bar graph display	No	
Multiple display	No	
With display backlight	No	
Measuring range selection	Automatic	
Current measuring range, AC	1E-05 - 300 Ampere	
True RMS measurement	No	
Voltage measurement, AC	No	
Voltage measurement, DC	No	
Resistance measuring range	No	
Temperature measurement	No	
Capacitance measurement	No	
Frequency measurement	No	
Power measuring	No	
Leakage current measuring	Yes	
Harmonics measurement	No	
Measurement in cables with for- and back conductor	No	
Jaw opening	40 Millimetre	
Version as adapter to connect to multi meter	No	
Interface	No	
Measuring circuit category	CAT III	

Continuity test	No