



ELIT iFlex 3000v2

Flexible current clamp adapter with 4mm connection to multimeter, 3000AAC

Technical description

Three current ranges: 30A, 300A and 3000A. Output ranges of 1mV / A. 51cm probe length. Measuring diameter 17cm Surge category: Measuring hose: CAT IV 600V Measuring box: CAT III 600V Fits all electrical systems. Large bandwidth. Low battery indication. Comes with 2 x 1.5V AA battery and user manual.

Advantages:



Product name/ Art.nr/ GTIN	ELIT iFlex 3000v2/ 10300009/ 7070810006953
According to:	---
Indication	Analogue
Analogue bar graph display	No
Multiple display	No
With display backlight	No
Measuring range selection	Manual
Current measuring range, AC	0,5 - 3000 Ampere
Type of current	AC
True RMS measurement	Yes
Voltage measurement, AC	No
Voltage measurement, DC	No
Resistance measuring range	No
Temperature measurement	No
Capacitance measurement	No
Frequency measurement	No
Power measuring	No
Leakage current measuring	No
Harmonics measurement	Yes
Measurement in cables with for- and back conductor	No
Jaw opening	170 Millimetre
Version as adapter to connect to multi meter	Yes
Interface	No

Measuring circuit category	CAT IV
Max. voltage measuring circuit category	600 Volt
Continuity test	No
Degree of protection (IP)	IP40