



ELIT 365, CAT IV 600V,

Durable current clamp with 2m drop test and IP54. Versatile with Low Z and Inrush function. Ø33mm

Technical description

ELIT 365 is the latest addition to ELIT's current clamp series. New useful features such as:

Low Z - Low input impedance to exclude ghost voltage (induced) when measuring.

LPF - Low-pass filter for i.a. to filter out superharmonic tensions e.g. when measuring on frequency converters.

AC + DC - Allows you to measure both the AC and DC components on one signal at a time.

Inrush - Capture of starting currents on motors. The RMS value of the first 100ms at start-up is automatically kept in the display, at the same time as normal operating current will be shown.

µA - Input for measuring micro-amperes. Well suited for measuring on sensors.

IP54, 2m drop and CAT IV 600V - These parameters in combination make the pliers applicable in all areas in all environments.

The above functions combined with all the functions expected from a current clamp with multimeter functions in the professional class make ELIT 365 a very versatile tool.



Advantages:

Product name/ Art.nr/ GTIN	
ELIT 365, CAT IV 600V, IP54/ 10300030/ 7070811209414	
According to:	---
Indication	Digital
Analogue bar graph display	Yes
Multiple display	Yes
With display backlight	Yes
Measuring range selection	Manual/automatic
Current measuring range, DC	0,01 - 600 Ampere
Current measuring range, AC	0,01 - 600 Ampere
True RMS measurement	Yes
Voltage measurement, AC	Yes
Voltage measurement, DC	Yes
Resistance measuring range	Yes
Temperature measurement	Yes
Capacitance measurement	Yes
Frequency measurement	Yes
Power measuring	No
Leakage current measuring	No
Harmonics measurement	No
Measurement in cables with for- and back conductor	No
Jaw opening	35 Millimetre
Version as adapter to connect to multi meter	No
Interface	No

Measuring circuit category	CAT IV
Continuity test	Yes